

# MALISH FLOOR MACHINE DUST SKIRT



## FEATURES

- Available in 17" and 20" diameter
- Clever design with a floating skirt and vacuum port
- Over 4" of adjustable skirting which allows the dust skirt to conform to the highs and lows of floor capturing maximum amount of dust
- Easily attaches to a single disc floor machines using a VELCRO® quick-connect system

## INSTRUCTIONS FOR USE



1. Clean the floor machine housing (bumper) of any residual dirt and debris.



2. Remove VELCRO® with white adhesive backing from the inside of the dust skirt. Then remove the backing from the VELCRO® exposing the adhesive for attaching to the housing of floor machine.



3. Apply VELCRO® strip to the middle/upper half of the outside diameter of the floor machine housing (bumper).



4. Apply the Malish Dust Skirt with vacuum port positioned at the bottom left of the floor machine.



5. Attach wet/dry vacuum hose to the vacuum port of dust skirt.

## APPLICATIONS

- Useful for any application that generates dust



FOR INFO AND PRICING: [WWW.MALISHEUROPE.COM](http://WWW.MALISHEUROPE.COM) OR EMAIL: [RENES@MALISH.COM](mailto:RENES@MALISH.COM)

EUROPE - NORTH AMERICA - ASIA